



PVC Material Specifications		
Specifications	Value	ASTM
Control Tensile Strength PSI	6332	D-638
Weathered Tensile Strength PSI	6690	D-638
Percentage Change	+5.6%	D-638
Rate of Burning	0.0 mm/min	D-635
Smoke Density	63.5	D-2843
Self Ignition	380 C	D-1929

BILL OF MATERIALS		
ITEM	QTY	PART DESCRIPTION
1	2	0.875" U-CHANNEL
2	2	GALV. U-CHANNEL FOR 2X6 RAIL
3	15	47.75" T&G BOARD
4	30	0.75" SCREW
5	2	5"X5"X9' HEAVY WALL POST
6	2	2"X6"X93.5 RAILS
7	1	2"X3.5"X93.5" AS TOP RAIL
8	6	3" SCREW
9	27	1.5"X1.5" PICKETS
10	27	1.5"X1.5" PYRAMID CAP

F S C
FRED S. CARDWELL, P.E.
 FLORIDA# 15607
 1000 SOUTH BELCHER RD
 BLDG-A / UNIT #11
 LARGO, FLORIDA 33771
 VOICE: 727-524-1905
 FAX: 727-524-1299

THIS DRAWING IS NOT VALID UNLESS SIGNED IN PURPLE INK

MIAMI-DADE COUNTY 75MPH WIND LOAD FOR HIGH VELOCITY HURRICANE ZONE

STYLE#	DESCRIPTION
V3706-6	Vinyl 6' High Tongue & Groove with Victorian Stepped Top

Eastern Wholesale Fence, Inc. - 274 Middle Island Rd. Medford, NY 11763

Illusions
 VINYL FENCE

www.IllusionsFence.com

SHEET

10

SHEET 10 OF 18

10-08-09

WIND TEST 0609 ILLUSIONS FENCE ©2009